

ID (mm)	OD (mm)	Weight (kg/m)	Tolerance (μm)
32	42	4.57	+39 - 0
40	50	5.56	+39 - 0
45	55	6.17	+39 - 0
50	60	6.79	+39 - 0
50	65	10.65	+39 - 0
55	65	7.41	+46 - 0
55	70	11.57	+46 - 0
63	73	8.40	+46 - 0
63	75	10.22	+46 - 0
65	80	13.43	+46 - 0
70	82	11.26	+46 - 0
70	85	14.35	+46 - 0
75	90	15.28	+46 - 0
80	90	10.49	+46 - 0
80	92	12.74	+46 - 0
80	95	16.20	+46 - 0
90	102	14.20	+54 - 0
90	105	18.06	+54 - 0
95	110	18.95	+54 - 0
100	115	19.91	+54 - 0
100	120	27.16	+54 - 0

ID (mm)	OD (mm)	Weight (kg/m)	Tolerance (μm)
100	125	34.72	+54 - 0
110	130	29.63	+54 - 0
120	140	32.10	+54 - 0
120	145	40.90	+54 - 0
125	145	33.34	+63 - 0
125	150	42.44	+63 - 0
130	150	34.57	+63 - 0
140	160	37.04	+63 - 0
145	170	57.41	+63 - 0
150	170	39.51	+63 - 0
160	180	41.98	+63 - 0
160	185	53.24	+63 - 0
180	200	46.92	+63 - 0
180	205	59.42	+63 - 0
185	220	84.84	+72 - 0
200	230	79.63	+72 - 0
220	270	150.97	+72 - 0
250	298.5	169.46	+72 - 0
300	355	224.60	+81 - 0

* stock available subject to prior sales

PRAXIS